Geared Trolley TSG KITO

Product information

General: Geared trolley with capacity from 0,125 tons up to 5 tons. The standard trolley includes rubber bumper, safety lug and suspender.

... *Read more*



Material: Pressed steel plate.
Marking: According to standard, CE-marked
Temperature range: -40°C up to +60°C (–20°C up to + 40°C for the use with a electric chain hoist)
Standard: EN 13157

Safety factor: 4:1

Forankra Polska
office@forankra.pl
+48 91 418 25 91

© October 2026 - All Rights Reserved

Forankra
Zabezpieczamy wszystko w transporcie™

Geared Trolley TSG KITO

Technical data

Part code	WLL ton	Beam width mm	Model	Chain length m
43030047B	0.125	164-305	W30	3
43030033B	0.125	58-163	Standard	3
16.05TSG002SC030	0.25	58-163	Standard	3
43030048B	0.25	164-305	W30	3
43030049B	0.5	164-305	W30	3
43030035B	0.5	58-163	Standard	3
43030036B	1	164-305	W30	3
43030050B	1	58-163	Standard	3
43030051B	1.5	205-305	W30	3
43030038B	1.5	82-204	Standard	3
43030053B	2	205-305	W30	3
43030040B	2	82-204	Standard	3
43030052B	2.5	205-305	W30	3
43030039B	2.5	82-204	Standard	3
43030054B	3	205-305	W30	3
43030041B	3	82-204	Standard	3
43030028B	5	205-305	W30	3,5
43030042B	5	100-204	Standard	3.5
16.05TSG0752C030	7.5	221-305	W30	3,5
16.05TSG075SC030	7.5	150-220	Standard	3.5
16.05TSG1002C030	10	221-305	W30	4,0
16.05TSG100SC030	10	150-220	Standard	4
16.05TSG1502C030	15	221-305	W30	4.5
16.05TSG150SC030	15	150-220	Standard	4.5
16.05TSG2002C030	20	221-305	W30	4.5
16.05TSG200SC030	20	150-220	Standard	4.5
16.05TSG3002C030	30	191-305	W30	4.5
16.05TSG300SC030	30	190	Standard	4.5

Forankra Polska
office@forankra.pl
+48 91 418 25 91

© October 2026 - All Rights Reserved