Horizontal Lifting Clamp FHX/FHSX

Product information



For horizontal lifting and transporting of steel plates and other non-deflecting materials. Jaw openings available from: 0 to 150 mm. Only to be used and only sold in pairs.

Model FHX: Standard clamp

Model FHSX: Clamp with enlarged jaw opening.

- Compact design and high lifting capacity
- Lightweight design for easy handling
- Tough quality heavy duty welded body

... *Read more*

Marking: According to standard, CE-marked, Type, serial number, WLL, Jaw opening.
Temperature range: - 40°C up to +100°C
Standard: EN 13155
Note: Must always be used in pairs (or multiple pairs)
Warning: Hardness level of the material surface may not exceed 37 HrC (345 Hb, 1166 N/mm2)

Попередження: рівень твердості поверхні матеріалу не повинен перевищувати 37 HrC (345 Hb, 1166 Н/мм2)


Forankra Polska
office@forankra.pl
+48 91 418 25 91

© October 2026 - All Rights Reserved

Forankra
Zabezpieczamy wszystko w transporcie™

Horizontal Lifting Clamp FHX/FHSX

Blueprint



Technical data

Part code	Code	WLL ton	Jaw width mm	V mm	S mm	W mm	T mm	H mm	X mm	U mm	Y mm	Weight kg
44010012B	1 FHX	1	0-35	140	99	10	25	11.5	65	188	15	2.6
44010047B	2 FHX	2	0-60	180	118	15	30.5	19.5	90	287	16	7
44010010B	2 FHSX	2	0-100	180	120	15	30.5	19.5	90	383	15	9.2
44010123B	3 FHX	3	0-60	180	118	20	30.5	19.5	90	291	16	8
44010055B	3 FHSX	3	0-100	180	120	20	30.5	19.5	90	387	15	10
44010089B	4 FHX	4	0-60	220	145	25	30.5	19.5	105	304	20	13
44010083B	4 FHSX	4	0-100	220	145	25	30.5	19.5	105	414	20	15
44010090B	6 FHX	6	0-60	220	145	25	30.5	19.5	110	307	20	14
44010084B	6 FHSX	6	0-100	220	145	25	30.5	19.5	120	414	20	16.5
44010124B	8 FHX	8	0-60	225	135	35	30.5	19.5	120	336	30	19
44010011B	8 FHSX	8	0-100	225	135	35	30.5	19.5	120	428	30	21
44010120B	10 FHX	10	0-60	225	135	35	30.5	19.5	120	336	30	19
44010072B	10 FHSX	10	0-100	225	135	35	30.5	19.5	120	428	30	22
44010093B	12 FHX	12	0-60	225	135	35	30.5	19.5	120	336	30	19
44010118B	12 FHSX	12	0-100	225	135	35	30.5	19.5	120	428	30	22
44010121B	15 FHX	15	0-60	262	147	35	43	21.5	160	344	35	30
44010119B	15 FHSX	15	0-150	350	240	35	45	27.5	140	665	35	53
44010122B	25 FHX	25	0-60	262	147	40	43	21.5	175	349	35	33

Forankra Polska
office@forankra.pl
+48 91 418 25 91

© October 2026 - All Rights Reserved