

Lifting Eye TP



Product information

The Theipa Point lifting eye is a rotatable attachment point that can be loaded in all directions. The eye is equipped with a ball bearing swivel so that it can be rotated under load and this ensures that the eye is in the right direction when loaded.

The link can pivot and therefore also can be folded aside when not in use.

The Crimpfeature ("pinch spots") on the link prevents the link from kinking and the galvanized coating provides an optimal corrosion protection

Available on request:

- Different thread and/or lengths
- Equipped with RFID Chip
- Thread adapter: female-female or female-male

Material: Eye and swivel of alloy steel

Marking: CE-marked, UKCA-marked, WLL

Temperature range: -40° up to +400°C







Finish: Galvanized coating - Paint

Note: The surface that the lifting eyes shall be attached to shall be flat and tolerate the load it is going to be exposed to.

Safety factor: 4:1

Code	WLL ton	Thread mm	Tightening torque Nm	Pitch DIN 13	b mm	bi mm	d mm	e mm	g mm	SW mm	t mm	t1 mm	ø mm	Weight kg	Delivery time
TP 0,7	0.5	M 10 x 55	40	1.5	36.5	32	M 10	55	48	34	41	55	13	7.04	12

Technical data

Anschlagart Kind of attachment									
Stück Number of pieces		1	1	2	2	2	3 o. 4		
Neigungswinkel Inclination angle		0°	90°	0°	90°	0°–45°	45°–60°	0°–45°	45°–60°
Bezeichnung Gewindeausführung Code	Thread version	Tragfähigkeit WLL*							
		t	t	t	t	t	t	t	t
TP 0,7	M 6	0,5	0,12	1,0	0,24	0,17	0,12	0,26	0,18
	M 8	0,6	0,3	1,2	0,6	0,4	0,3	0,6	0,45
	M 10	1,0	0,5	2,0	1,0	0,7	0,5	1,0	0,75
	M 12	1,4	0,7	2,8	1,4	1,0	0,7	1,4	1,0
	M 14	2,0	1,0	4,0	2,0	1,4	1,0	2,12	1,5
TP 1,4	M 16	2,8	1,4	5,6	2,8	2,0	1,4	3,0	2,12
	M 20	3,4	1,7	6,8	3,4	2,4	1,7	3,55	2,5
	M 24	3,4	1,7	6,8	3,4	2,4	1,7	3,55	2,5
TP 2,5	M 20	5,0	2,5	10,0	5,0	3,55	2,5	5,3	3,75
TP 4	M 24	8,0	4,0	16,0	8,0	5,6	4,0	8,5	6,0
	M 30	8,0	4,0	16,0	8,0	5,6	4,0	8,5	6,0
TP 6,7	M 30	12,0	6,7	24,0	13,4	9,5	6,7	14,0	10,0
TP 8	M 30	12,0	8,0	24,0	16,0	11,2	8,0	16,0	12,0
TP 10	M 36	15,0	10,0	30,0	20,0	14,0	10,0	21,2	15,0
TP 12,5	M 42	15,0	12,5	30,0	25,0	17,0	12,5	25,0	18,0
	M 45	15,0	12,5	30,0	25,0	17,0	12,5	25,0	18,0
	M 48	15,0	12,5	30,0	25,0	17,0	12,5	25,0	18,0
TP 17	M 42	20,0	13,0	40,0	26,0	18,0	13,0	27,0	19,0
	M 45	25,0	17,0	50,0	34,0	23,5	17,0	35,0	25,0
	M 48	25,0	17,0	50,0	34,0	23,5	17,0	35,0	25,0
	M 56	25,0	18,0	50,0	36,0	25,0	18,0	37,5	26,5
TP 20	M 64	25,0	20,0	50,0	40,0	28,0	20,0	42,5	30,0
TP 28	M 64	32,5	28,0	65,0	56,0	39,0	28,0	58,0	42,0
	M 72	32,5	28,0	65,0	56,0	39,0	28,0	58,0	42,0
	M 80	32,5	28,0	65,0	56,0	39,0	28,0	58,0	42,0
TP 35	M 72	50,0	35,0	100,0	70,0	49,5	35,0	74,2	52,5
	M 80	50,0	35,0	100,0	70,0	49,5	35,0	74,2	52,5
	M 90	50,0	35,0	100,0	70,0	49,5	35,0	74,2	52,5
TP 40	M 72	60,0	40,0	120,0	80,0	56,6	40,0	84,9	60,0
TP 48	M 80	60,0	48,0	120,0	96,0	67,9	48,0	102,0	72,0
TP 50	M 90	60,0	50,0	120,0	100,0	70,7	50,0	106,0	75,0
	M 100	60,0	50,0	120,0	100,0	70,7	50,0	106,0	75,0

*Gesamte Tragfähigkeit pro Anwendungsfall/Total WLL per application

Bei unsymmetrischer Lastverteilung gelten für 2- und 3/4-Strängige Anschlagketten (-punkte) die Tragfähigkeiten für 1-Strängige bei 90°.

Die Tragfähigkeiten ab TP 35 gelten für die Ausführung mit den neuen Quetschmarken.

In the case of an unsymmetrical load distribution, the working load limit applicable to the 2- and 3/4-leg slings (attachment points) are the same as for 1-leg sling at 90°.

The working load limits from TP 35 onwards apply specifically to the version with the new crimpfeature.

Blueprint

