Concrete lifting eye clutch

Product information



A universal concrete lifting eye clutch used for lifting and handling concrete elements containing separate lifting anchors. The lower part of the round main body of the lifting clamp has a pocket that fits into the correspondingly shaped end of the T-lifting anchor in the semicircular recess of the concrete element. Connecting and disconnecting is quick and easy and can be done in practically one movement. The lifting clutchs are suitable for use in axial (vertical)/diagonal and lateral 90° load directions.

Load groups:

- **NS8BEL1,3:** 1,0-1,3 t
- **NS8BEL2,5**: 1,5-2,5 t
- **NS8BEL5**: 3-5 t
- **NS8BEL10**: 6-10 t

... *Read more*

Material: Steel
Marking: CE-mark
Finish: Painted, yellow
Note: The product does not include a lifting anchor, and anchors are not included in the Haklift's product range
Warning: Only use lifting anchors and lifting clutches that are compatible (load rating/dimensions) and designed to be used with each other (type/design) to ensure safe use and correct fit

Forankra Polska
office@forankra.pl
+48 91 418 25 91

© November 2026 - All Rights Reserved

Forankra
Zabezpieczamy wszystko w transporcie™

Concrete lifting eye clutch

Technical data

Part code	WLL ton	Weight kg
42120034F	2.5	1.5
42120035F	5	3.3
42120036F	10	10

Forankra Polska
office@forankra.pl
+48 91 418 25 91

© November 2026 - All Rights Reserved