Wire Rope Lifting Sling WLS-113

Product information



Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm2*
(*ø 3mm - ø 7mm rope constrcution: 6x19M WSC 1960 N/mm2)
Design: Both ends mechanically spliced thimbles.

Load table at Technical Data -> Show table

Please specify the needed (working) length and eye diam/length with your request.

Other rope construction and/or end-terminations such as master links, shackles, hooks, etc.. possible on request. In that case, please check our website for more standard wire rope slings. You can also contact us to discuss the possible options or specify it with your request.

... *Read more*

Forankra Polska
office@forankra.pl
+48 91 418 25 91

© November 2026 - All Rights Reserved

Forankra
Zabezpieczamy wszystko w transporcie™

Wire Rope Lifting Sling WLS-113

Technical data

Diameter mm	WLL ton
3	0.12
4	0.21
5	0.32
6	0.47
7	0.64
8	0.82
9	1.04
10	1.28
11	1.55
12	1.84
13	2.17
14	2.51
16	3.3
18	4.1
20	5.1
22	6.2
24	7.38
26	8.66
28	10.04
32	13.12
36	16.59
40	20.56
44	24.78
48	29.55

Forankra Polska
office@forankra.pl
+48 91 418 25 91

© November 2026 - All Rights Reserved