

## Thimble DIN 6899B



### Product information

**Design:** Pressed of profile steel.

**Finish:** Galvanized

Part code	Rope Ø range mm	a mm	b mm	c mm	d mm	e mm	Weight kg/100pc	Delivery time
10.25B6889903	2.5	3	22	19	12	1.6	0.6	12
10.25B6889904	3.5	4	26	21	13	1.6	0.7	12
10.25B6889905	4	5	32	23	14	1.9	0.9	12
10.25B6889906	5	6	38	25	16	2.4	1.8	12
10.25B6889907	6	7	44	28	18	2.4	1.9	12
10.25B6889908	7	8	51	32	20	2.8	2.7	12
10.25B6889910	9	10	57	38	24	3.1	4.1	12

10.25B6889912	11	12	64	45	28	3.3	6.9	12
10.25B6889913	12	13	70	48	30	3.3	7.6	12
10.25B6889914	13	14	76	51	32	3.7	9.2	12
10.25B6889916	15	16	83	58	36	3.8	16.4	12
10.25B6889917	16	17	89	61	38	4.7	19	12
10.25B6889918	17	18	95	64	40	4.7	20.3	12
10.25B6889920	18	20	102	72	45	5.7	27.3	12
10.25B6889922	20	22	114	80	50	5.7	28.6	12
10.25B6889924	22	24	127	90	56	6.5	44.8	12
10.25B6889926	24	26	140	99	62	6.8	57.7	12
10.25B6889928	26	28	152	112	70	8	72	12
10.25B6889936	34	36	216	160	100	8.5	176	12
10.25B6889938	36	38	229	176	110	8.5	195	12
10.25B6889940	38	40	241	184	115	10.5	292	12
10.25B6889942	40	42	254	192	120	10.5	320	12
10.25B6889945	42	45	305	240	150	10.5	364	12
10.25B6889950	47	50	360	265	160	12	535	12
10.25B6889960	57	60	380	275	170	12	790	12
10.25B6889965	63	65	420	300	180	13	830	12
10.25B6889975	72	75	460	350	200	15	1,200	12
10.25B6889999	97	100	550	380	220	20	3,050	12

## Blueprint

