



Plate hook KWB BH/S

Product information

Link for webbing slings mounted in one V/S-half. Reduced risk of damage due to wide surface.

Material: Alloy steel

Marking: According to standard, Code and grade

Finish: Violet powder coated.

Standard: EN 1677-1

(+ 25% WLL)

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 10

| Part code | Code | WLL ton | EWL mm | For chain Ø mm | a mm | b mm | c mm | d mm | e mm | g mm | s mm | Weight kg | Delivery time |
|-----------|-------------|------------|-----------|-------------------|---------|---------|---------|---------|---------|---------|---------|--------------|---------------|
| 42050626B | RSK/S-08-10 | 2.5 | 66 | 8 | 29 | 68 | 12 | 10 | 66 | 18 | 18 | 0.36 | 2 |
| 42050110B | RSK/S-10-10 | 4 | 81 | 10 | 40 | 82 | 15 | 13 | 81 | 24 | 21 | 0.69 | 12 |
| 42050627B | RSK/S-13-10 | 6.7 | 104 | 13 | 44 | 101 | 20 | 17 | 104 | 28 | 28 | 1.32 | 12 |
| 42050628B | RSK/S-16-10 | 10 | 113 | 16 | 47 | 110 | 21 | 21 | 113 | 33 | 40 | 1.83 | 12 |
| 42050112B | RSK/S-22-10 | 19 | 190 | 22 | 110 | 215 | 34 | 25 | 190 | 51 | 58 | 7.98 | 12 |

Blueprint

