



4 Special Clevis Sub-Assembly GTVK/SUN

Product information

General: For 3 and 4-leg slings with shortening element.

Temperature range: -40 °C up to 200 °C

Safety factor: 4:1

Grade: 12

| Part code | Code | Chain diameter | WLL ton | EWL | can be used with single hook acc. DIN15401 up to nr. | WLL 45- 60° ton | d mm | t mm | w mm | e mm | Weight kg | Delivery time |
|-----------|---------------|----------------|---------|-----|--|-----------------|------|------|------|------|-----------|---------------|
| 42060037B | GTVK/SUN 4-7 | 7 | 5 | 368 | 10 | 3.55 | 27 | 190 | 110 | 368 | 6.35 | 12 |
| 42060038B | GTVK/SUN 4-8 | 8 | 6.3 | 368 | 10 | 4.5 | 27 | 190 | 110 | 368 | 6.39 | 12 |
| 42060017B | GTVK/SUN 4-10 | 10 | 10.6 | 433 | 12 | 7.5 | 30 | 190 | 110 | 433 | 10.94 | 12 |
| 42060039B | GTVK/SUN 4-13 | 13 | 17 | 616 | 12 | 11.8 | 38 | 275 | 150 | 616 | 25.35 | 12 |
| 42060040B | GTVK/SUN 4-16 | 16 | 25.6 | 658 | 12 | 18.3 | 38 | 275 | 150 | 658 | 37.17 | 12 |

Blueprint

