



1 Special Clevis Sub-Assembly GTVK/SUN

Product information

General: For 1-leg slings with shortening element.

Temperature range: -40 °C up to 200 °C

Safety factor: 4:1

Grade: 12

| Part code | Code | Chain diameter | WLL ton | EWL | can be used with single hook acc. DIN15401 up to nr. | d mm | t mm | w mm | e mm | Weight kg | Delivery time |
|-----------|---------------|----------------|---------|-----|--|------|------|------|------|-----------|---------------|
| 42060005B | GTVK/SUN 1-7 | 7 | 2.36 | 244 | 4 | 14 | 120 | 70 | 244 | 1.22 | 12 |
| 42060031B | GTVK/SUN 1-8 | 8 | 3 | 264 | 5 | 17 | 140 | 80 | 264 | 1.48 | 12 |
| 42060032B | GTVK/SUN 1-10 | 10 | 5 | 318 | 6 | 19 | 160 | 95 | 318 | 2.63 | 12 |
| 42060033B | GTVK/SUN 1-13 | 13 | 8 | 391 | 10 | 27 | 190 | 110 | 391 | 6.11 | 12 |
| 42060034B | GTVK/SUN 1-16 | 16 | 12.2 | 423 | 12 | 30 | 190 | 110 | 423 | 8.9 | 12 |

Blueprint

