

Chain sling G80 3-leg with sling hooks

Product information

High quality 3-leg chain sling equipped with sling hooks. Manufactured with high quality grade 80 components. Chain slings are one of the most popular tools for lifting loads in various industries. They are ideal as auxiliary equipment for transporting and lifting loads. All our slings meet the requirements of EU standards and have CE marking. The main advantages of our lifting slings are high resistance to mechanical damage and temperature, they are 100% safe and offer high WLL with low own weight.

Marking: According to standard, CE-marked

Standard: EN 818-4

Safety factor: 4:1

Класс: 8



Код товара	Chain diameter mm	WLL ton	EWL m	Bec kg	Delivery time
42070400W	6	2,36	1	13,75	12
42071269W	6	2,36	2	14,45	12
42071255W	6	2,36	0,5	15,95	12
42070409W	6	2,36	1,5	16,65	12
42071265W	6	2,36	2,5	17,35	12
42071273W	6	2,36	3,5	19,75	12
42071280W	6	2,36	4	20,95	12

42071277W	6	2,36	3	21,95	12
42071288W	6	2,36	6	24,05	12
42071284W	6	2,36	5	26,75	12
42071292W	8	4,25	0,5	16,753	12
42071299W	8	4,25	1	18,778	12
42070366W	8	4,25	1,5	20,803	12
42071306W	8	4,25	2	22,828	12
42071303W	8	4,25	2,5	24,853	12
42071314W	8	4,25	3	26,878	12
42071310W	8	4,25	3,5	28,903	12
42071317W	8	4,25	4	30,928	12
42071321W	8	4,25	5	34,978	12
42071325W	8	4,25	6	39,028	12
42071139W	10	6,7	0,5	18,475	12
42071147W	10	6,7	1	21,7	12
42071143W	10	6,7	1,5	24,925	12
42071154W	10	6,7	2	28,15	12
42071151W	10	6,7	2,5	31,375	12
42071161W	10	6,7	3	34,6	12
42071157W	10	6,7	3,5	37,825	12
42071164W	10	6,7	4	41,05	12
42071168W	10	6,7	5	47,5	12

42071172W	10	6,7	6	53,95	12
42071176W	13	11,2	0,5	31,8	12
42071184W	13	11,2	1	37,05	12
42071180W	13	11,2	1,5	42,3	12
42071192W	13	11,2	2	47,55	12
42071188W	13	11,2	2,5	52,8	12
42071200W	13	11,2	3	58,05	12
42071196W	13	11,2	3,5	63,3	12
42071203W	13	11,2	4	68,55	12
42071207W	13	11,2	5	79,05	12
42071211W	13	11,2	6	89,55	12
42071223W	16	17	1	59,3	12
42071219W	16	17	1,5	67,55	12
42071231W	16	17	2	75,8	12
42071227W	16	17	2,5	84,05	12
42071239W	16	17	3	92,3	12
42071235W	16	17	3,5	100,55	12
42071243W	16	17	4	108,8	12
42071247W	16	17	5	125,3	12
42071251W	16	17	6	141,8	12

Blueprint

