

## Chain Sling G80 3-leg with Safety Hooks

### Product information

High quality 3-leg chain sling equipped with self-locking hooks. Manufactured with high quality grade 80 components. Chain slings are one of the most popular tools for lifting loads in various industries. They are ideal as auxiliary equipment for transporting and lifting loads. All our slings meet the requirements of EU standards and have CE marking. The main advantages of our lifting slings are high resistance to mechanical damage and temperature, they are 100% safe and offer high WLL with low own weight.

**Marking:** According to standard, CE-marked

**Standard:** EN 818-4

**Safety factor:** 4:1

**Класс:** 8



Код товара	Chain diameter mm	WLL ton	EWL m	Bec kg	Delivery time
42070690W	6	2,36	0,5	14,79	12
42070694W	6	2,36	1	15,99	12
42070692W	6	2,36	1,5	17,19	12
42070698W	6	2,36	2	18,39	12
42070696W	6	2,36	2,5	19,59	12
42070702W	6	2,36	3	20,79	12
42070700W	6	2,36	3,5	21,99	12

42070704W	6	2,36	4	23,19	12
42070706W	6	2,36	5	25,59	12
42070708W	6	2,36	6	27,99	12
42070710W	8	4,25	0,5	19,413	12
42070714W	8	4,25	1	21,438	12
42070712W	8	4,25	1,5	23,463	12
42070718W	8	4,25	2	25,488	12
42070716W	8	4,25	2,5	27,513	12
42070722W	8	4,25	3	29,538	12
42070720W	8	4,25	3,5	31,563	12
42070724W	8	4,25	4	33,588	12
42070726W	8	4,25	5	37,638	12
42070728W	8	4,25	6	41,688	12
42070630W	10	6,7	0,5	22,675	12
42070634W	10	6,7	1	23,35	12
42070632W	10	6,7	1,5	31,675	12
42070638W	10	6,7	2	32,35	12
42070636W	10	6,7	2,5	33,025	12
42070640W	10	6,7	3,5	42,025	12
42070642W	10	6,7	3	43,9	12
42070644W	10	6,7	4	47,8	12
42070646W	10	6,7	5	51,7	12

42070648W	10	6,7	6	63,25	12
42070650W	13	11,2	0,5	34,8	12
42070654W	13	11,2	1	40,05	12
42070652W	13	11,2	1,5	45,3	12
42070658W	13	11,2	2	50,55	12
42070656W	13	11,2	2,5	55,8	12
42070662W	13	11,2	3	61,05	12
42070660W	13	11,2	3,5	66,3	12
42070664W	13	11,2	4	71,55	12
42070666W	13	11,2	5	82,05	12
42070668W	13	11,2	6	92,55	12
42070674W	16	17	1	55,7	12
42070672W	16	17	1,5	63,95	12
42070678W	16	17	2	72,2	12
42070676W	16	17	2,5	80,45	12
42070682W	16	17	3	88,7	12
42070680W	16	17	3,5	96,95	12
42070684W	16	17	4	105,2	12
42070686W	16	17	5	121,7	12
42070688W	16	17	6	138,2	12

## Blueprint

