

Chain Sling G80 1-leg with Sling Hook



Product information

High quality 1-leg chain sling equipped with sling hook. Manufactured with high quality grade 80 components. Chain slings are one of the most popular tools for lifting loads in various industries. They are ideal as auxiliary equipment for transporting and lifting loads. All our slings meet the requirements of EU standards and have CE marking. The main advantages of our lifting slings are high resistance to mechanical damage and temperature, they are 100% safe and offer high WLL with low own weight.

Marking: According to standard, CE-marked

Standard: EN 818-4

Safety factor: 4:1

Класс: 8

Код товара	Chain diameter mm	WLL ton	EWL m	Bec kg	Delivery time
42070191W	6	1,12	0,5	13,49	12
42070149W	6	1,12	1	13,89	12
42070927W	6	1,12	1,5	14,29	12
42070125W	6	1,12	2	14,69	12
42070931W	6	1,12	2,5	15,09	12
42070938W	6	1,12	3	15,49	12
42070935W	6	1,12	3,5	15,89	12

42070942W	6	1,12	4	16,29	12
42070946W	6	1,12	5	17,09	12
42070950W	6	1,12	6	17,89	12
42070174W	8	2	0,5	10,781	12
42070119W	8	2	1	11,456	12
42070957W	8	2	1,5	12,131	12
42070224W	8	2	2	12,806	12
42070964W	8	2	2,5	13,481	12
42070011W	8	2	3	14,156	12
42070190W	8	2	3,5	14,831	12
42070975W	8	2	4	15,506	12
42070979W	8	2	5	16,856	12
42070983W	8	2	6	18,206	12
42070812W	10	3,15	0,5	18,875	12
42070162W	10	3,15	1	19,95	12
42070395W	10	3,15	1,5	21,025	12
42070163W	10	3,15	2	22,1	12
42070822W	10	3,15	2,5	23,175	12
42070832W	10	3,15	3	24,25	12
42070828W	10	3,15	3,5	25,325	12
42070836W	10	3,15	4	26,4	12
42070839W	10	3,15	5	28,55	12

42070843W	10	3,15	6	30,7	12
42070847W	13	5,3	0,5	16,35	12
42070854W	13	5,3	1	18,1	12
42070279W	13	5,3	1,5	19,85	12
42070861W	13	5,3	2	21,6	12
42070858W	13	5,3	2,5	23,35	12
42070869W	13	5,3	3	25,1	12
42070865W	13	5,3	3,5	26,85	12
42070872W	13	5,3	4	28,6	12
42070876W	13	5,3	5	32,1	12
42070880W	13	5,3	6	35,6	12
42070892W	16	8	1	28,1	12
42070888W	16	8	1,5	30,85	12
42070900W	16	8	2	33,6	12
42070896W	16	8	2,5	36,35	12
42070908W	16	8	3	39,1	12
42070904W	16	8	3,5	41,85	12
42070912W	16	8	4	44,6	12
42070916W	16	8	5	50,1	12
42070920W	16	8	6	55,6	12

Blueprint

