Lifting Eye Bolt RUD RS, UNC/UN thread

Product information



- considerably higher WLL in comparison to DIN 580
- clear marking of the minimum WLL
- comprehensive range of threads

... *Read more*

Marking: According to standard
Standard: EN 1677-1

Safety factor: 4:1


Forankra Polska
office@forankra.pl
+48 91 418 25 91

© November 2026 - All Rights Reserved

Forankra
Zabezpieczamy wszystko w transporcie™

Lifting Eye Bolt RUD RS, UNC/UN thread

Blueprint



Technical data

WLL ton	Thread Inch	A mm	B mm	C mm	D mm	E mm	T mm	Bec kg
0,1	1/4 -20	12	11	10	25	25	34	0,1
0,2	5/16 -18	12	11	10	25	25	34	0,1
0,25	3/8 -16	15	11	10	25	25	34	0,1
0,4	7/16 -14	18	13	12	30	30	41	0,18
0,4	1/2 -13	18	13	12	30	30	41	0,18
0,75	9/16 -12	22	15	14	35	35	48	0,3
1	5/8 -11	24	15	14	35	35	48	0,3
1,2	3/4 -10	30	17	16	40	40	55	0,47
1,5	7/8 -9	34	21	20	50	50	70	0,8
2	1 -8	36	21	20	50	50	70	0,85
2,5	1 1/8 -7	45	26	24	60	60	85	1,6
2,5	1 1/8 -8	45	26	24	60	60	85	1,6
3	1 1/4 -7	46	26	24	60	60	85	1,6
3	1 1/4 -8	45	26	24	60	60	85	1,6
3	1 3/8 -6	55	43	38	90	100	130	6,1
4	1 1/2 -6	58	43	38	90	100	130	6,2
4	1 1/2 -8	58	43	38	90	100	130	6,5
6	1 3/4 -5	67	43	38	90	100	130	6,3
6	1 3/4 -8	67	43	38	90	100	130	6,5
8	2 -4.5	67	43	38	90	100	130	6,5

Forankra Polska
office@forankra.pl
+48 91 418 25 91

© November 2026 - All Rights Reserved