

High Dynamic Schakle RUD VIP-Mini-Coupling

Product information



High tensile version with an integrated safety thread in the shackle bracket. Smooth bolt support in the shackle on both sides. The bolt is turnable. No bending strength in the thread (only a securing function).

Optimal adaptation - max. mouth width with the smallest shackle bolt. Owing to the turned clevis connection, it is extensively resistant to bending. Long term securing by driving in the pre-assembled tensioning sleeve.


Special thread, thus distinctive in comparison to other shackle bolts. Pre-assembled connecting bolt and tensioning sleeve.

... [Read more](#)

Safety factor: 4:1

High Dynamic Schakle RUD VIP-Mini-Coupling

Blueprint



Technical data

Код	WLL ton	A mm	B mm	C mm	D mm	E mm	F mm	G mm	T mm	Bec kg
VMKS-4	0,63	14	8	20	10	30	36	21	42	0,11
VVGSC-6	1,5	17	8	22	10	21	40	28	36	0,13
VVGSC-8	2,5	21	10	26	12	32	48	39	48	0,27
VVGSC-10	4	27	13	34	16	35	62	44	60	0,6
VVGSC-13	6,7	33	17	42	20	41	81	59	78	1,3
VVGSC-16	10	38	21	49	24	49	95	69	96	2,25
VVGSC-20	16	47	27	60	30	57	119	88	108	4,26
VVGSC-22	20	53	30	76	36	72	130	95	132	6,43