Lifting Point RUD VLBS

Product information



- Suspension ring pivots 180°
- Suspension ring & weld-on-block of the VLBS-U are undetachable
- Suspension ring can be angled into position (VLBS-U)

Available in with and without spring versions.

... *Read more*

Marking: CE-mark

Safety factor: 4:1.


Forankra Polska
office@forankra.pl
+48 91 418 25 91

© November 2026 - All Rights Reserved

Forankra
Zabezpieczamy wszystko w transporcie™

Lifting Point RUD VLBS

Blueprint



Technical data

Код товара	Код	WLL ton	Eye diameter mm	T mm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	Вес kg
11.427993115	VLBS-1,5t without spring	1,5	25	65	33	66	25	38	40	14	33	14	0,35
11.427995346	VLBS-2,5t without spring	2,5	27	75	38	77	28	45	47	16	40	16	0,53
11.427993116	VLBS-4t without spring	4	32	83	42	87	31	51	52	18	46	16	0,72
11.427993117	VLBS-6,7t without spring	6,7	44	117	61	115	44	67	73	24	60	22,5	1,89
11.427993118	VLBS-10t without spring	10	55	126	75	129	55	67	71	26,5	60	26,5	2,75
11.427993120	VLBS-16t without spring	16	69	176	96	192	70	100	106	40	90	26	7,1

Forankra Polska
office@forankra.pl
+48 91 418 25 91

© November 2026 - All Rights Reserved