



Lifting Eye RUD VRS-F Starpoint, UNC thread

Product information

- 360° adjustable in force direction
- several times higher WLL than the DIN 580 eye bolt
- Easy-Fit-Key for easy assembly and disassembly

Marking: CE-marked

Safety factor: 4:1

WLL ton	Thread Inch	B mm	C mm	D mm	E mm	G mm	I mm	K mm	L mm	N mm	T mm	Bec kg	Delivery time
0,4	3/8 -16	11	9	25	25	30	16,3	47	15	6,35	35	0,12	12
0,4	7/16 -14	11	9	25	25	30	16,3	47	15	6,35	35	0,12	12
0,75	1/2 -13	13	10	30	30	34	19,8	56	19	7,94	42	0,22	12
1,5	5/8 -11	15	13	35	36	40	23,5	65	24	9,53	49	0,33	12
2,3	3/4 -10	17	16	40	41	50	29,3	76	29	12,7	58	0,58	12
2,3	7/8 -9	17	16	40	41	50	29,3	76	33	12,7	58	0,61	12
3,2	1 -8	20	19	49	51	60	35	92	36	14,29	70	0,98	12
4,5	1 1/4 -7	26	24	60	66	75	44	114	48	15,88	87	2,08	12
7	1 1/2 -6	32	29	73	76	98	53	135	54	22,23	104	3,6	12
9	1 3/4 -5	37	33	84	86	111	62	158	63	25,4	121	4,95	12
12	2 -4.5	42	42	94	100	128	70	180	72	28,58	138	7,6	12

Blueprint

