

Eye Nut RUD VRM STARPOINT



Product information

Multi-directional threaded design, load rating up to six times the capacity of collared eye nuts.

Design: Octagonal lifting eye.

For bolts with min. quality class 10.9

Marking: According to standard, CE-marked

Standard: EN 1677-1

Safety factor: 4:1

Класс: 10

Код товара	Код	Diameter mm	WLL ton	Thread mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	I mm	K mm	L mm	N mm	T mm	Вес kg	Delivery time
-	VRM	-	0,1	M6	9	7	20	23	16	28	17	13	37	11	9	28	0,06	12
11.427992989	VRM	25	0,3	M8	11	9	25	25	21	30	21	16,3	47	14	12	35	0,1	12
11.427990311	VRM	25	0,4	M10	11	9	25	25	21	30	21	16,3	47	14	12	35	0,1	12
11.427990312	VRM	30	0,75	M12	13	10	30	30	24	34	25	19,8	56	17	14	42	0,18	12
11.427990314	VRM	35	1,5	M16	15	13	35	36	30	40	29	23,6	65	21	19	49	0,32	12
11.427990315	VRM	40	2,3	M20	17	16	40	41	37	50	35	29,3	76	23	24	58	0,48	12
11.427990316	VRM	48	3,2	M24	20	19	49	51	45	60	41	35,2	92	29	30	70	0,83	12
46040244B	VRM	60	4,5	M30	26	24	60	66	56	75	51	44	114	36	36	87	1,32	12

Blueprint

