

Lifting Eye RUD VRS STARPOINT

Product information




- 360° adjustable in force direction
 - several times higher WLL than the DIN 580 eye bolt
 - Easy-Fit-Key for easy assembly and disassembly available, look type VRS.F ... [Read more](#)
-

Safety factor: 4:1

Lifting Eye RUD VRS STARPOINT

Blueprint



Technical data

Код товара	WLL ton	B mm	C mm	D mm	E mm	G mm	I mm	K mm	L mm	M mm	N mm	T mm	Bec kg
42040255B	0,3	11	9	25	25	30	16,3	47	12	M8	6	35	0,11
-	0,4	11	9	25	25	30	16,3	47	15	M10	6	35	0,11
42040254B	0,75	13	10	30	30	34	19,8	56	18	M12	8	42	0,19
-	0,75	13	10	30	30	34	19,8	56	18	M14	8	42	0,2
-	1,5	15	13	35	36	40	23,5	65	24	M16	10	49	0,32
-	2,3	17	16	40	41	50	29,3	76	30	M20	12	58	0,54
-	3,2	20	19	49	51	60	35	92	36	M24	14	70	0,86
-	4,5	26	24	60	66	75	44	114	45	M30	17	87	1,5
-	7	32	29	73	76	98	53	135	54	M36	22	104	3,3