



## Lifting Eye Starpoint VRS-F with variable length

### Product information

- 360° adjustable in force direction
- several times higher WLL than the DIN 580 eye bolt
- Easy-Fit-Key for easy assembly and disassembly

**Safety factor:** 4:1

Код товара	WLL	B,	C,	D,	E,	G,	I mm	K,	L	M mm	N mm	T mm	Delivery time
-	0,4	11	9	25	25	30	16,3	47	16-70	M10	6	35	12
-	0,75	13	10	30	30	34	19,8	56	18-150	M12	8	42	12
11.408600272-035	1,5	15	13	35	36	40	23,5	65	35	M16	10	49	12
11.408600272-120	1,5	15	13	35	36	40	23,5	65	120	M16	10	49	12
-	1,5	15	13	35	36	40	23,5	65	24-120	M16	10	49	12
11.408600273-120	2,3	17	16	40	41	50	29,3	76	120	M20	12	58	12
11.408600273-160	2,3	17	16	40	41	50	29,3	76	160	M20	12	58	12
-	2,3	17	16	40	41	50	29,3	76	30-160	M20	12	58	12
-	3,2	20	19	49	51	60	35	92	36-140	M24	14	70	12
-	4,5	26	24	60	66	75	44	114	45-190	M30	17	87	12

# Blueprint

