Shortening Claw ICE IMVK

Product information



After decades of success, the VIP-Multi-Shortening claw has been further enhanced.

- Can be captively fitted along the chain leg.
- No additional chain and coupling components are required.
- It can be moved to any position along the chain leg.
- The ideal link shaped chain pocket provides an optimal fitting for the chain thus no reduction of the WLL.
- A robust safety bolt with a spring prevents the accidental loosening of the fitted chain in both loaded and unloaded conditions.

... *Read more*

Marking: According to standard
Standard: DIN 5692

Safety factor: 4:1
Класс: 12


Forankra Polska
office@forankra.pl
+48 91 418 25 91

© November 2026 - All Rights Reserved

Forankra
Zabezpieczamy wszystko w transporcie™

Shortening Claw ICE IMVK

Blueprint



Technical data

Код	Chain diameter mm	WLL ton	A mm	B mm	C mm	D mm	T mm	Bec kg
IMVK 6	6	1,8	38	32	41	35	66	0,28
IMVK 8	8	3	47	40	54	47	88	0,61
IMVK 10	10	5	60	51	67	60	110	1,6
IMVK 13	13	8	77	65	87	77	143	2,6
IMVK 16	16	12,5	95	81	110	95	176	4,8

Forankra Polska
office@forankra.pl
+48 91 418 25 91
© November 2026 - All Rights Reserved