Weld-on Lifting Ring RUD VLBS-U with spring

Product information



- Suspension ring pivots 180°
- Suspension ring & weld-on-block of the VLBS-U are undetachable
- Suspension ring can be angled into position (VLBS-U)

Clamping spring works as a noise reduction and holds the suspension ring in the requested position; therefore simple hinge of lashion mean possible.

... *Read more*

Marking: According to standard
Standard: EN 1677-1

Safety factor: 4:1

Forankra Polska
office@forankra.pl
+48 91 418 25 91

© November 2026 - All Rights Reserved

Forankra
Zabezpieczamy wszystko w transporcie™

Weld-on Lifting Ring RUD VLBS-U with spring

Blueprint



Technical data

Код товара	Код	WLL ton	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	T mm	Вес kg
11.427994830	VLBS-U-2,5t with spring	2,5	38	77	28	45	47	16	40	16	75	0,53
11.427993036	VLBS-U-4t with spring	4	42	87	31	51	52	18	46	16	83	0,72
11.427993037	VLBS-U-6,7t with spring	6,7	61	115	44	67	73	24	60	22,5	117	1,89
06.VLBSU10	VLBS-U-10t with spring	10	75	129	55	67	71	26,5	60	26,5	126	2,76

Forankra Polska
office@forankra.pl
+48 91 418 25 91

© November 2026 - All Rights Reserved