



Black Belt Sling™ Extreema® with Dyneema® core

Product information

These Extreema® HMPE soft slings have an extensive track record and a solid global footprint in the heavy lift industry. The Black Belt Sling™ has unparalleled load-bearing capacity, ensuring the safe and efficient lifting of even the heaviest loads.

The core is made of Bio Based Dyneema®, which makes it up to 15 times stronger than steel on a weight-to-weight basis.

The sleeve is an orange PES inner sleeve and is covered with a black knitted Cordura® outer sleeve, which is known for its resistance to abrasions, tears, and scuffs. The black sleeve is repairable.

When to choose this product

Best for:

- Heavy lifting with cranes, shackles, and large connection points
- Environments with high abrasion and repeated handling

Features:

- Lightweight and flexible, easy to handle
- Repairable sleeve
- Does not absorb water
- Floats on water
- Abrasion, tearing and scuff resistant
- Sustainable
- High pressure resistant
- EWL: 0,5m – 65m
- Standard with RFID

Marking: CE-marked

Safety factor: 7:1

Код товара	WLL ton	EWL m	Delivery time
-	12	6	12
12.20EXCO0150XXX	15	-	12
-	15	13	12
-	16	1	12
-	18	7,5	12
12.20EXCO0200XXX	20	-	12
-	20	4,8	12
-	20	5,14	12
-	20	1,49	12
-	20	1,75	12
-	20	1,91	12
-	20	2,42	12
-	25	2,23	12
-	25	4	12
-	25	4,75	12
-	25	5	12
-	25	1	12
-	25	3	12
12.20EXCO0300050	30	5	12
12.20EXCO0300XXX	30	-	12
-	30	10,53	12

-	30	2,01	12
-	30	2,75	12
-	30	3	12
-	30	4	12
-	30	8	12
-	30	1	12
-	30	1,5	12
-	35	1,5	12
-	35	1,9	12
-	35	3,47	12
-	35	3,6	12
-	35	4,5	12
-	35	5,5	12
12.20EXCO0400050	40	5	12
12.20EXCO0400XXX	40	-	12
-	40	1,73	12
-	40	10,2	12
-	40	2,68	12
-	40	3	12
-	40	3,25	12
-	40	4,88	12
-	40	5,18	12
-	40	7,96	12

-	40	9,7	12
-	40	6,5	12
-	45	1,8	12
-	45	4,5	12
-	45	5	12
-	45	5,75	12
-	45	7	12
12.20EXCO0500XXX	50	-	12
-	50	1	12
-	50	1,25	12
-	50	1,5	12
-	50	2,4	12
-	50	2,9	12
-	50	3	12
-	50	3,1	12
-	50	3,42	12
-	50	3,5	12
-	50	4	12
-	50	4,6	12
-	50	5	12
-	50	7	12
-	50	14	12
-	55	7,7	12

-	56	10	12
-	56	16	12
-	60	1	12
-	60	2	12
-	60	2,4	12
-	60	2,5	12
-	60	3	12
-	60	3,2	12
-	60	3,3	12
-	60	3,35	12
-	60	3,55	12
-	60	5	12
-	60	5,8	12
-	60	9	12
-	65	14	12
-	65	2,5	12
-	65	5	12
-	70	2,5	12
12.20EXCO0750050	75	5	12
12.20EXCO0750XXX	75	-	12
-	75	0,5	12
-	75	10	12
-	75	8	12

-	80	2,07	12
-	80	5,5	12
-	80	6,95	12
-	80	1,5	12
-	80	14	12
-	90	14	12
-	90	5	12
-	90	9	12
12.20EXCO1000050	100	5	12
12.20EXCO1000XXX	100	-	12
-	100	10	12
-	100	12	12
-	100	3	12
-	100	7,3	12
-	120	2	12
-	120	27	12
-	120	3	12
-	120	4,5	12
-	120	7	12
12.20EXCO1250500	125	5	12
12.20EXCO1250XXX	125	-	12
-	125	12,8	12
-	125	2	12

-	125	4	12
-	125	6,4	12
-	125	8	12
12.20EXCO1500500	150	5	12
12.20EXCO1500XXX	150	-	12
-	150	2,5	12
-	150	4,5	12
-	150	4,73	12
-	150	6,8	12
-	160	27	12
-	160	7	12
-	180	14	12
-	180	5	12
-	180	6	12
-	185	12,87	12
-	195	14,75	12
-	195	16	12
12.20EXCO2000500	200	5	12
12.20EXCO2000XXX	200	-	12
-	200	1,5	12
-	200	12,06	12
-	200	4	12
-	200	6	12

-	200	8	12
-	217,4	3	12
-	217,4	3,51	12
-	220	4	12
-	250	3	12
-	250	5	12
-	250	7	12
-	269,8	11,7	12
-	269,8	5,85	12
-	270	4,41	12
-	290	3,05	12