



Multi driven hoist

Product information



Small aluminium multi driven chain hoists with a wide range of lifting applications. Can be used with a drill machine. The drill can be connected with 1.5-3 mtr long operating cable in the hoist, so the load can be easily lifted and lowered with the help of the drill machine.

Can also be used directly from the shaft (8 mm hexagonal) coming out of the side of the hoist frame, either with a drill or manually with a comb or 1/2" ratchet handle. The lifting and lowering speed is directly dependent on the rotation speed of the drill, so the speed is always controlled by the drill's own controls.

The standard lifting height is 3 mtr. Other lifting heights can be supplied quickly. The upper and lower hooks are equipped with a swivel.

Marking: CE-marked

Код товара	WLL ton	Lifting height m	Number of falls	Lifting speed m/min.	Load chain mm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H min mm	Bec kg	Delivery time
43050245F	0,25	3	1	2,2	3,2 x 9	109	84	25	1 500	16	30	8	240	3,5	12
43050246F	0,5	3	1	2,2	4,3 x 12	122	102	30	1 500	16	30	8	270	5,45	12
43050250F	1	3	2	1,1	4,3 x 12	122	102	32,3	1 500	16	30	8	350	9,15	12

Blueprint

