

Geared trolley

Product information



Geared trolley for IPE and T beams. The trolley moves on the beam by pulling the hand chain. The wheels are equipped with duration lubricated ball bearings. The width of the trolley can be adjusted by a threaded rod (10 and 20 t models with washers, in the picture). The hoist or lifter can be attached directly to the trolley eye with a hook or a shackle.

... [Read more](#)


Marking: According to standard, CE-marked

Standard: EN 13157

Safety factor: 4:1

Geared trolley

Blueprint



Technical data

Код товара	WLL ton	Beam width mm	Minimum radius mm	A mm	B mm	C mm	D, mm	E mm	F mm	G, mm	H, mm	J mm	Бес kg
43030016F	1	58-220	700	353,5	238	183	17	31	~3	68	95	37	12,5
43030017F	2	66-220	900	362	277	208	20	31	~3	80	108	48	17
43030018F	3	74-220	1 200	406,5	324	249	26	31	~3	100	131	56	28
43030019F	5	90-220	1 000	434,5	373	296,5	28	40	~5	120	154	65	45
43030013F	10	125-203	1 300	487,5	455	490	82	36,5	~5	-	-	120	93
SIVA200HKS	20	136-203	4 700	523	642	622	110	54	~5	-	-	150	247,5