



Lifting eye screw DIN 580

Product information

Lifting eye screws for vertical lifting

Marking: According to standard, CE-marked

Standard: DIN 580

Safety factor: 4:1

Код товара	WLL ton	Thread mm	Packing	Thread pitch mm	d1 mm	d2 mm	d3 mm	d4 mm	h mm	k mm	l mm	Bec kg	Delivery time
46040030F	0,08	M6	50	1	M6	20	36	20	18	8	13	0,045	12
46040031F	0,14	M8	50	1,25	M8	20	36	20	18	8	13	0,05	12
46040019F	0,23	M10	50	1,5	M10	25	45	25	22,5	10	17	0,09	12
46040020F	0,34	M12	25	1,75	M12	30	54	30	26	12	20,5	0,16	12
46040032F	0,34	M14	25	2	M14	35	63	35	30,5	14	27	0,24	2
46040021F	0,7	M16	10	2	M16	35	63	35	30,5	14	27	0,24	12
46040022F	1,2	M20	10	2,5	M20	40	72	40	35	16	30	0,36	12
46040023F	1,8	M24	1	3	M24	50	90	50	45	20	36	0,72	12
46040041F	3,2	M33	1	3,5	M33	65	108	60	55	24	45	1,3	12
46040024F	3,2	M30	1	3,5	M30	65	108	60	55	24	45	1,32	12
46040043F	4,6	M39	1	4	M39	75	126	70	65	28	54	2,02	12
46040042F	4,6	M36	1	4	M36	75	126	70	65	28	54	2,08	12
46040045F	6,3	M45	1	4,5	M45	85	144	80	75	32	63	3,04	12
46040044F	6,3	M42	1	4,5	M42	85	144	80	75	32	63	3,11	12
46040047F	8,6	M52	1	5	M52	100	166	90	85	38	68	4,95	12
46040046F	8,6	M48	1	5	M48	100	166	90	85	38	68	5,02	12
46040048F	11,5	M56	1	5,5	M56	110	184	100	95	42	78	6,69	12
46040049F	16	M64	1	6	M64	120	206	110	105	48	90	9,3	12

Blueprint

