

Lifting eye screw with swivel, grade 80

Product information



Lifting screw with swivel for all lifting directions. Also available with longer 120 mm thread.


... [Read more](#)

Marking: According to standard, CE-marked
Standard: EN 1677-1

Safety factor: 4:1

Lifting eye screw with swivel, grade 80

Blueprint



Technical data

Код товара	WLL ton	Thread mm	Eye diameter mm	diameter eye inside mm	Thread pitch mm	b mm	g mm	t mm	e mm	d mm	Bec kg
46030006F	0,45	M10	14	55x30	1,5	36	51	41	18	M10	0,43
46030007F	0,5	M12	14	55x30	1,75	36	51	41	18	M12	0,44
46030008F	1,1	M16	14	55x30	2	36	52	42	20	M16	0,46
46030009F	1,1	M16	14	55x30	2	36	52	42	120	M16	0,46
46030010F	2	M20	16	70x34	2,5	50	68	56	30	M20	0,96
46030019F	2	M20	16	70x34	2,5	50	68	56	120	M20	0,96
46030020F	3,2	M24	18	85x37	3	57	78	65,5	120	M24	1,45
46030012F	3,2	M24	18	85x37	3	57	78	65,5	40	M24	1,45
46030023F	5,3	M30	20	85x37	3,5	66	97	80,5	120	M30	2,17
46030013F	5,3	M30	20	85x37	3,5	66	97	80,5	35	M30	2,17
46030014F	8	M30	22	115x50	3,5	80	112	92	35	M30	3,57
46030024F	8	M30	22	115x50	3,5	80	112	92	120	M30	3,57
46030015F	8	M36	22	115x50	4	80	109	89,5	50	M36	4,17
46030026F	8	M36	22	115x50	4	80	109	89,5	120	M36	4,17
46030027F	10	M42	25	115x50	4,5	80	109	89,5	50	M42	3,67
46030016F	10	M48	25	115x50	5	80	109	89,5	50	M48	4,02
46030028F	10	M45	25	115x50	4,5	80	109	89,5	60	M45	4,17
46030017F	15	M56	32	152x70	5,5	117	310	280	84	M56	11,6