



Turnable lifting point, grade 80

Product information

- turnable lifting point for all lifting directions.
- eye turns to the direction of the load
- bolts also available with 120 mm thread
- bolt grade 10.9

Marking: According to standard, CE-marked

Standard: EN 1677-1

Safety factor: 4:1

Код товара	WLL ton	Thread mm	Packing Qty.	Thread length mm	Tightening torque Nm	Thread pitch mm	A, B, C, D, EL	F, G, H, S	SW mm	L1 mm	Bec kg	Packing Qty.	Delivery time
46010199F	0,3	M8	40	11	30	1,25	33 37 35 14 11	98 57 36 6	13	47	0,5	40	12
46010209F	0,3	M8	-	120	30	1,25	33 37 35 14 120	98 57 36 6	13	156	0,5	-	12
46010200F	0,63	M10	40	16	60	1,5	33 37 36 14 16	98 57 36 6	17	52	0,5	40	12
46010210F	0,63	M10	-	120	60	1,5	33 37 36 14 120	98 57 36 6	17	156	0,5	-	12
46010201F	1	M12	40	18	100	1,75	33 37 44 14 18	98 57 36 8	19	54	0,5	40	2
46010211F	1	M12	-	120	100	1,75	33 37 44 14 120	98 57 36 8	19	156	0,5	-	12
46010202F	1,5	M16	40	24	150	2	33 37 46 14 24	98 57 36 10	24	60	0,5	40	12
46010212F	1,5	M16	-	120	150	2	33 37 46 14 120	98 57 36 10	24	156	0,5	-	12
46010203F	2,5	M20	10	30	250	2,5	50 54 57 17 30	140 82 44 12	30	74	1,3	10	2
46010213F	2,5	M20	-	120	250	2,5	50 54 57 17 120	140 82 44 12	30	164	1,3	-	12
46010204F	4	M24	10	36	400	3	50 54 59 17 36	140 82 44 14	36	80	1,4	10	12
46010214F	4	M24	-	120	400	3	50 54 59 17 120	140 82 44 14	36	164	1,4	-	12
46010205F	5	M30	6	48	500	3,5	60 65 81 23 48	170 99 62 17	46	110	3,1	6	12
46010215F	5	M30	-	120	500	3,5	60 65 81 23 120	170 99 62 17	46	182	3,1	-	12
46010206F	8	M36	4	62	800	4	77 85 101 27 62	225 124 78 22	55	140	5,8	4	12
46010216F	8	M36	-	120	800	4	77 85 101 27 120	225 124 78 22	55	198	5,8	-	12
46010207F	15	M42	2	63	1 500	4,5	95 104 112 36 63	256 158 86 24	65	149	10,8	2	12
46010217F	15	M42	-	120	1 500	4,5	95 104 112 36 120	256 158 86 24	65	206	10,8	-	12
46010208F	20	M48	2	72	2 000	5	95 104 120 36 72	259 158 90 27	75	162	11,6	2	12
46010218F	20	M48	-	120	2 000	5	95 104 120 36 120	259 158 90 27	75	210	11,6	-	12

Blueprint

