

Shackles, SAE - bow model with locking

Product information

Shackles approved for lifting. Bow shackles are suitable for use when more than one attachment is to be made to the body (multi-leg systems), or to allow freedom of movement in the plane of the bow. Locking bolt shackles are recommended for long-term and permanent installations, or when there is a natural tendency for the pin to unscrew (rotate) in the application, or when the shackle cannot be observed under operation.

Marking: According to standard, CE-marked

Standard: US. FED. SPEC. RR-C-271F

Safety factor: 6:1



| Код товара | WLL ton | Size inch | A, | B, | C, | D, | E, | F, | G, | H, | N mm | Вес kg | Delivery time |
|------------|---------|-----------|-----|----|-----|----|-----|-----|-----|-----|------|--------|---------------|
| 46010034F | 0,5 | 1/4 | 12 | 8 | 29 | 7 | 20 | 16 | 33 | 47 | 7 | 0,05 | 12 |
| 46010037F | 0,75 | 5/16 | 14 | 10 | 31 | 8 | 22 | 19 | 38 | 53 | 8 | 0,1 | 2 |
| 46010041F | 1 | 3/8 | 17 | 11 | 37 | 10 | 26 | 23 | 45 | 63 | 10 | 0,15 | 2 |
| 46010054F | 1,5 | 7/16 | 19 | 13 | 43 | 11 | 30 | 27 | 52 | 74 | 11 | 0,22 | 2 |
| 46010063F | 2 | 1/2 | 21 | 16 | 48 | 13 | 34 | 30 | 59 | 84 | 13 | 0,36 | 2 |
| 46010071F | 3,25 | 5/8 | 27 | 19 | 61 | 16 | 43 | 38 | 75 | 106 | 18 | 0,76 | 12 |
| 46010078F | 4,75 | 3/4 | 32 | 23 | 72 | 19 | 51 | 46 | 89 | 126 | 21 | 1,23 | 2 |
| 46010083F | 6,5 | 7/8 | 37 | 26 | 84 | 23 | 58 | 53 | 102 | 148 | 25 | 1,79 | 2 |
| 46010089F | 8,5 | 1 | 43 | 29 | 96 | 26 | 69 | 61 | 119 | 167 | 27 | 2,57 | 2 |
| 46010092F | 9,5 | 1-1/8 | 46 | 32 | 108 | 29 | 74 | 69 | 131 | 190 | 32 | 3,75 | 2 |
| 46010047F | 12 | 1-1/4 | 52 | 35 | 119 | 32 | 83 | 76 | 146 | 210 | 35 | 5,31 | 2 |
| 46010194F | 13,5 | 1-3/8 | 57 | 38 | 133 | 35 | 92 | 84 | 162 | 233 | 38 | 7,18 | 2 |
| 46010059F | 17 | 1-1/2 | 61 | 42 | 146 | 38 | 99 | 92 | 175 | 254 | 41 | 9,43 | 2 |
| 46010067F | 25 | 1-3/4 | 73 | 51 | 178 | 45 | 127 | 106 | 225 | 313 | 57 | 15,4 | 2 |
| 46010074F | 35 | 2 | 83 | 57 | 197 | 51 | 146 | 122 | 256 | 348 | 61 | 23,7 | 12 |
| 46010171F | 55 | 2-1/2 | 105 | 70 | 267 | 67 | 184 | 145 | 327 | 453 | 80 | 44,61 | 2 |
| 46010100F | 85 | 3 | 127 | 83 | 330 | 76 | 200 | 165 | 365 | 546 | 92 | 70 | 12 |
| 46010186F | 120 | 3-1/2 | 133 | 96 | 372 | 92 | 229 | 203 | 419 | 626 | 105 | 120 | 12 |

Blueprint

