



## Spur Gear Hand Winch TL1000-1500 Painted

### Інформація про товар

This spur gear winch is fast, easy and can be mounted on both walls and floors. The free spool option is therefore also available for this winch. In addition to IP54 water resistance, this winch is also available in stainless steel 304.

- robust and safe lifting and pulling winch
- protection classification IP54
- load pressure brake with double ratchet system for safe stable hold of the load in any position
- cable outlet upwards, downwards or at the left
- closed gearbox to protect against environmental influence
- adjustable crank
- suitable for wall and floor mounting
- 1 layer of paint

#### Options:

- zinc-plated finish 6 - 8 micron (EV)
- 2 layers of paint (2L)
- stainless steel grade 304 (SST304)
- 2 drum compartment (2D)
- free-spooling device for pulling applications. To disengage the drum (FS)
- ATEX certified zone 2 and 22 (EX)

CE II 3G Ex IIC T4 Gc, -20°C<T amb <+70°C  
CE II 3D Ex IIIC T135°C Dc, -20°C<T amb <+70°C

**Маркування:** Згідно зі стандартом, CE-marked

**Стандарт:** EN 13157

**Коефіцієнт запасу міцності:** 4:1

Код	Вантажопідйомність тон	Rope Ø mm	Rope capacity m	Capacity 1st layer kg	Capacity top layer kg	Вара кг	Delivery time
TL1000	1	8	33	1 000	614	27	12
TL1500	1,5	10	21	1 500	927	27,5	12

## Креслення

