



Heavy Duty Air Chain Hoists Red Rooster TMH (10.000, 15.000 & 20.000 kg)

Інформація про товар

The Red Rooster TMH series air chain hoists have the highest lifting speed with the lowest headroom on the hoist market. With M4 classification of mechanism this hoist is extremely reliable. This hoist will guarantee the continuity of your process. The TMH hoists are designed with a supporting eye for easy installation.

Standard features:

- Precise variable speed control (cord- and pendant control)
- Optimum control of the load, very precise positioning
- Main air shut off valve
- Mechanical end stop system
- Load limiter built-in without loss of headroom
- Working air pressure 0,4 - 0,63 MPa (4-6,3 bar)
- Piped away exhaust air

ATEX:

- According to EC Directive 94/9/EC (Ex Classification)

Recommended:

We strongly recommend using an air handling unit, e.g. from SMC (offered separately).

Маркування: Згідно зі стандартом, CE-marked

Стандарт: EN 14492-2

Вантажопідйомність тон	Тип	Chain falls	Швидкість підйому м/хв	Air consumption lowering (l/sec)	Air consumption lifting l/sec	Швидкість підйому м/хв	Lowering speed with max.load m/min	A	B	C	D,	E	F	G, H,	Imm	J	K	L	Mmm	Nmm	Bara	Delivery time	
								мм	мм	мм	мм	мм	мм	мм	мм	мм	мм	мм	мм	мм	кг		
10	Cord control	2	3,3	71,7	58,3	1,6	3,2	860	463	188	275	221	60	214	266	315	65	ø60	45	351	ø61	206	12
10	Pendant control	2	3,3	71,7	58,3	1,6	3,2	860	463	188	275	221	60	214	266	315	65	ø60	45	351	ø61	206	12
15	Cord control	3	2,2	71,7	58,3	1,05	2,1	880	695	635	255	270	52	250	266	315	67	ø84	58	436	ø84	316	12
15	Pendant control	3	2,2	71,7	58,3	1,05	2,1	880	695	635	255	270	52	250	266	315	67	ø84	58	436	ø84	316	12
20	Cord control	4	1,6	71,7	58,3	0,8	1,6	1 028	500	150	350	-	64	315	326	387	80	ø110	78	475	ø110	466	12
20	Pendant control	4	1,6	71,7	58,3	0,8	1,6	1 028	500	150	350	-	64	315	326	387	80	ø110	78	475	ø110	466	12

Креслення

