



Heavy Duty Air Chain Hoists Red Rooster TMH (37.500 & 45.000 kg)

Інформація про товар

The Red Rooster TMH series air chain hoists have the highest lifting speed with the lowest headroom on the hoist market.

Standard features:

- Precise variable speed control (cord control)
- Optimum control of the load, very precise positioning
- Main air shut off valve
- Mechanical end stop system
- Load limiter built-in without loss of headroom
- Low noise level (84 dBA)
- Working air pressure 0,4 - 0,63 MPa (4-6,3 bar)
- Piped away exhaust air

ATEX:

- According to EC Directive 94/9/EC (Ex Classification)

Recommended:

We strongly recommend using an air handling unit, e.g. from SMC (offered separately).

Маркування: Згідно зі стандартом, CE-marked

Стандарт: EN 14492-2

Вантажопідйомність тон	Тип	Chain falls	Швидкість підйому м/хв	Air consumption lowering (l/sec)	Air consumption lifting l/sec	Швидкість підйому м/хв	Lowering speed with max.load m/min	A	B	C	D, E	F	G, H, I	J	K	L	Mmm	Nmm	Omm	Pmm	Qmm	Bara	Delivery time
37,5	Cord control	3	1,8	180	108	0,9	2	1 440	1 150	557,55	92,51	118 90	830 380	675 125	118 545	352	256	112	112	300	1 300	12	
37,5	Pendant control	3	1,8	180	108	0,9	2	1 440	1 150	557,55	92,51	118 90	830 380	675 125	118 545	352	256	112	112	300	1 300	12	
45	Cord control	3	1,8	167	108	0,65	1,8	1 440	1 150	557,55	92,51	118 90	830 380	675 125	118 545	352	256	112	112	300	1 300	12	
45	Pendant control	3	1,8	167	108	0,65	1,8	1 440	1 150	557,55	92,51	118 90	830 380	675 125	118 545	352	256	112	112	300	1 300	12	

Креслення

