



Lifting Magnet NEO

Інформація про товар

The Neo magnet is widely used for handling ferromagnetic materials in the metal industry – in workshops, on building sites, in warehouses for semi-finished steel products, when handling steel workpieces, tools, sheets, metal profiled sections, tubes, and bars. The Neo permanent lifting magnet is intended for use in production plants where an emphasis is placed on enhanced safety. Thanks to strong neodymium magnets, it has a higher lifting capacity than other magnets with similar dimensions.

It easily handles flat, round, and cylindrical loads with emphasis on safety and convenience. Each magnet is tested for break-away force with an air gap to simulate real operating conditions. The magnet body is highly resistant to mechanical damage, the bearings are secured, so their life span is longer. The magnet features a versatile lifting eye design for easy suspension. The magnet enables load handling at a maximum temperature of 80°C.

Features:

- Simple Easy Switch control – the lifting magnet can be switched easily, quickly, and safely.
- The Air Gap test – a tear-off test is carried out with the air gap - we place emphasis on higher safety in real operating conditions.
- Robust lifting eye made of stainless steel.
- 5-year warranty for the magnetic system.
- Capacity table for easy reference right on the magnet body.
- The magnet meets the 3+ safety factor - verified by the tear-off test.
- A compact body with only two recessed screws.

Маркування: Згідно зі стандартом

Стандарт: EN 13155

Коефіцієнт запасу міцності: 3:1

Код товару	Код	Вантажопідйомність тон	Eye diameter mm	WLL round materials t	W mm	L	H, mm	Вага кг	Delivery time
44030031F	NEOL150	0,15	10	0,065	60	93	120	3	12
44030039F	NEOL300	0,3	16	0,15	100	152	180	10	12
44030052B	NEOL600	0,6	20	0,3	120	246	180	21	12
44030037B	NEOL1000	1	20	0,5	146	306	236	40	12
44030044B	NEOL1500	1,5	20	0,75	165	374	273	69	12
44030037F	NEOL2000	2	20	1	165	478	273	90	12

Креслення

