



Manhole Clamp

Інформація про товар

The manhole clamp is used for the transport and laying of manholes. No adjustment of the clamping range is necessary. Accidents caused by incorrect adjustment are excluded. Due to the holdfast application the clamp must not be lifted when applying and disconnecting.

Features:

- Simple applying and disconnecting by means of holdfast application: clamp must not be lifted manually
- No adjustment of the clamping range
- Huge multiplication guarantees optimum safety
- Manhole clamp SZA for manholes and cones according to DIN 4034 Part 1 and 2
- With spring tension
- With web sling or high-strength chains

Коефіцієнт запасу міцності: 5:1

| Код товару | Код | Вантажопідйомність тон | Jaw width мм | Вага кг | Delivery time |
|-------------------|------------|---|-------------------------------|--------------------------|----------------------|
| 44000177B | SZM 1 | 1 | 40-120 | 16 | 12 |
| 44000178B | SZM 1.5 | 1,5 | 40-120 | 28 | 12 |
| 44000179B | SZML 1.5 | 1,5 | 40-120 | 29 | 12 |
| 44000184B | SZM 1.5 K | 1,5 | 40-120 | 32 | 12 |
| 44000180B | SZA 2 | 2 | 60-180 | 28 | 12 |
| 44000185B | SZA 2K | 2 | 60-180 | 31 | 12 |
| 44000181B | SZA 3 | 3 | 60-180 | 40 | 12 |
| 44000182B | SZAL 3 | 3 | 60-180 | 41 | 12 |
| 44000186B | SZA 3 K | 3 | 60-180 | 45 | 12 |
| 44000187B | SZAL 3 K | 3 | 60-180 | 47 | 12 |
| 44000183B | SZA 4 | 4 | 60-180 | 55 | 12 |